



Up to 14 SEER • From 18K to 60K BTU



Heat & Cool

Heat pump air conditioners can both heat and cool. Both Heat Pump and Cooling Only top discharge models available.



Warranty

Each unit has 7 years for parts and 10 years for the compressor. Warranty registration is required.



Quieter Operation

Factory installed discharge muffler to ensure quiet and stable operation.



Heat Pump

Model	Unit	A14CV4H4M18 A14EU4H4M18	A14CV4H4M24 A14EU4H4M24	A14CV4H4M30 A14EU4H4M30	A14CV4H4M36 A14EU4H4M36	A14CV4H4M42 A14EU4H4M42	A14CV4H4M48 A14EU4H4M48	A14CV4H4M60 A14EU4H4M60
Power Supply	V/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60
Heating Capacity (Min-Max)	Btu/h	17,200	22,400	29,000	34,600	41,000	47,000	56,000
Heating Current Input	A	10.4	13.4	16.5	19.4	21.6	24.6	29.6
Air Flow Volume	CFM	600	820	1,050	1,180	1,430	1,510	4,250
EER	(Btu/h)/W	12	11.5	12	12	11.5	11.5	12
SEER	-	14	14	14	14	14	14	14
INDOOR UNIT	Sound Pressure Level (H/M/L)	45/42/38	48/47/42	50/48/44	50/48/44	51/50/46	54/52/49	54/52/49
	Dimension (WxHxD)	18-1/8 x 41-3/8 x 20-1/2	19-5/8 x 46-1/2 x 21-5/8	19-5/8 x 46-1/2 x 21-5/8	19-5/8 x 46-1/2 x 21-5/8	22 x 54-1/2 x 24	22 x 54-1/2 x 24	22 x 54-1/2 x 24
	Package Dimension (WxHxD)	21-1/32 x 42-3/4 x 24-3/16	22-9/16 x 47-7/8 x 25-3/8	22-9/16 x 47-7/8 x 25-3/8	22-9/16 x 47-7/8 x 25-3/8	25 x 55-7/8 x 27-3/4	25 x 55-7/8 x 27-3/4	25 x 55-7/8 x 27-3/4
	Net Weight	104	125	128	128	159	159	159
	Gross Weight	117	141	143	143	177	177	177
OUTDOOR UNIT	Sound Pressure Level	62	62	64	64	67	67	67
	Dimension (WxHxD)	23-5/8 x 24-15/16 x 23-5/8	23-5/8 x 24-15/16 x 23-5/8	28 x 24-15/16 x 28	29-1/8 x 24-15/16 x 29-1/8	28 x 33-3/16 x 28	28 x 33-3/16 x 28	29-1/8 x 33-3/16 x 29-1/8
	Package Dimension (WxHxD)	24-3/4 x 26-1/4 x 24-3/4	24-3/4 x 26-1/4 x 24-3/4	29 x 26-1/4 x 29	30-1/4 x 26-1/4 x 30-1/4	29 x 34-1/2 x 29	29 x 34-1/2 x 29	30-1/4 x 34-1/2 x 30-1/4
	Net Weight	137	139	152	168	201	203	227
	Gross Weight	143	146	161	177	212	214	238
Refrigerant	-	R410A	R410A	R410A	R410A	R410A	R410A	R410A
PIPE CONNECTION	Refrigerant Charge	oz	85	82	103	107	131	129
	Outer Diameter Liquid Pipe	inch	3/8	3/8	3/8	3/8	3/8	3/8
	Outer Diameter Gas Pipe	inch	3/4	3/4	3/4	3/4	7/8	7/8



Air-Con International, Inc.
1802 SW 2nd St
Pompano Beach, FL 33069
Ph: 954-771-1415



www.airconint.com

Air-Con International, Inc. - Miami
7108 NW 50th St
Miami, FL 33166
Ph: 786-238-7234

Up to 14 SEER • From 18K to 60K BTU



Cooling Only

Model		Unit	A14CV4C4M18 A14EU4C4M18	A14CV4C4M24 A14EU4C4M24	A14CV4C4M30 A14EU4C4M30	A14CV4C4M36 A14EU4C4M36	A14CV4C4M42 A14EU4C4M42	A14CV4C4M48 A14EU4C4M48	A14CV4C4M60 A14EU4C4M60
Power Supply	V/Ph/Hz		208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60	208-230/1/60
Cooling Capacity (Min-Max)	Btu/h		18,000	23,400	29,000	35,000	41,500	48,000	57,000
Cooling Current Input	A		10.4	13.4	16.5	19.4	21.6	24.6	29.6
Air Flow Volume	CFM		600	820	1,050	1,180	1,430	1,510	4,250
EER	(Btu/h)/W		12	11.5	12	12	11.5	11.5	12
SEER	-		14	14	14	14	14	14	14
INDOOR UNIT	Sound Pressure Level (H/M/L)	dB(A)	45/42/38	48/47/42	50/48/44	50/48/44	51/50/46	54/52/49	54/52/49
	Dimension (WxHxD)	inch	18-1/8 x 41-3/8 x 20-1/2	19-5/8 x 46-1/2 x 21-5/8	19-5/8 x 46-1/2 x 21-5/8	19-5/8 x 46-1/2 x 21-5/8	22 x 54-1/2 x 24	22 x 54-1/2 x 24	22 x 54-1/2 x 24
	Package Dimension (WxHxD)	inch	21-1/32 x 42-3/4 x 24-3/16	22-9/16 x 47-7/8 x 25-3/8	22-9/16 x 47-7/8 x 25-3/8	22-9/16 x 47-7/8 x 25-3/8	25 x 55-7/8 x 27-3/4	25 x 55-7/8 x 27-3/4	25 x 55-7/8 x 27-3/4
	Net Weight	lb	104	125	128	128	159	159	159
	Gross Weight	lb	117	141	143	143	177	177	177
OUTDOOR UNIT	Sound Pressure Level	dB(A)	62	62	64	64	67	67	67
	Dimension (WxHxD)	inch	23-5/8 x 24-15/16 x 23-5/8	23-5/8 x 24-15/16 x 23-5/8	28 x 24-15/16 x 28	29-1/8 x 24-15/16 x 29-1/8	28 x 33-3/16 x 28	28 x 33-3/16 x 28	29-1/8 x 33-3/16 x 29-1/8
	Package Dimension (WxHxD)	inch	24-3/4 x 26-1/4 x 24-3/4	24-3/4 x 26-1/4 x 24-3/4	29 x 26-1/4 x 29	30-1/4 x 26-1/4 x 30-1/4	29 x 34-1/2 x 29	29 x 34-1/2 x 29	30-1/4 x 34-1/2 x 30-1/4
	Net Weight	lb	137	139	152	168	201	203	227
	Gross Weight	lb	143	146	161	177	212	214	238
Refrigerant	-		R410A	R410A	R410A	R410A	R410A	R410A	
PIPE CONNECTION	Refrigerant Charge	oz	85	82	103	107	131	129	182
	Outer Diameter Liquid Pipe	inch	3/8	3/8	3/8	3/8	3/8	3/8	3/8
	Outer Diameter Gas Pipe	inch	3/4	3/4	3/4	3/4	3/4	7/8	7/8



Air-Con International, Inc.
1802 SW 2nd St
Pompano Beach, FL 33069
Ph: 954-771-1415



www.airconint.com

Air-Con International, Inc. - Miami
7108 NW 50th St
Miami, FL 33166
Ph: 786-238-7234

Up to 14 SEER • From 18K to 60K BTU



Air-Con International, Inc.
1802 SW 2nd St
Pompano Beach, FL 33069
Ph: 954-771-1415



www.airconint.com

Air-Con International, Inc. - Miami
7108 NW 50th St
Miami, FL 33166
Ph: 786-238-7234