

SKY_{pro}



INTERNATIONAL

Up to 23 SEER • From 9K to 36K BTU



Heat & Cool

Enjoy year round comfort with the ability to heat or cool your room or space. Can continue to heat in low ambient temperatures as low as -4 degrees Fahrenheit.



Inverter Technology

Units that use Inverter technology are more energy efficient than traditional ACs. This energy efficiency translates to extended unit life, quiet operation, and lower electricity bills.



Each unit is covered with our Industry Leading Warranty. *Registration requirements vary by state.*

For full warranty policy details, visit:

[airconint.com/
warranty-information](http://airconint.com/warranty-information)



Installation Kit Includes:

- Indoor Unit (Evaporator)
- Outdoor Unit (Condenser)
- Remote Control



Model	Unit	ASLEK4H4S09 ASLEC4H4S09 ASLCI4H4S09	ASLEK4H4S12 ASLEC4H4S12 ASLCI4H4S12	ASLEK4H4S18 ASLEC4H4S18 ASLCI4H4S18	ASLEK4H4S24 ASLEC4H4S24 ASLCI4H4S24	ASLEK4H4S36 ASLEC4H4S36 ASLCI4H4S36
Power Supply	V/Ph/Hz			208-230/1/60		
Cooling Capacity	Btu/h	9,000 (4,850-11,600)	12,000 (5,800-13,100)	18,000 (4,200-21,000)	24,000 (8,600-25,200)	36,000 (12,600-36,800)
Cooling Power Input	W	700	960	1420	1920	3380
Cooling Current Input	A	3.6	4.3	6.5	8.6	14.6
Heating Capacity (Min-Max)	Btu/h	10,000 (4,340-12,280)	12,000 (4,400-14,400)	19,000 (5,600-24,000)	24,000 (7,600-28,400)	36,000 (15,000-42,600)
Heating Power Input (Min-Max)	W	709	926	1,425	1,950	3,190
Heating Current Input	A	3.5	4.1	6.3	8.7	14
Air Flow Volume (H/M/L)	CFM	309/274/232	324/294/235	588/500/394	647/530/400	941//794/676
EER	(Btu/h)/W	12.86	12.5	12.68	12.5	10.65
SEER	-	22	23	22	19	19.5
CASSETTE UNIT						
Sound Pressure Level (H/M/L)	dB(A)	38/34/31	42/37/33	38/36/34	44/40/38	49/43/39
Dimension (WxDxH)	inch	22 1/2 x 22 1/2 x 8 1/2	22 1/2 x 22 1/2 x 8 1/2	33 1/8 x 33 1/8 x 9 3/4	33 1/8 x 9 3/4 x 33 1/8	33 1/8 x 33 1/8 x 11 3/4
Package Dimension (WxDxH)	inch	28-3/4 x 26-1/4 x 11-1/2	28-3/4 x 26-1/4 x 11-1/2	39-1/4 x 37-5/8 x 14-5/8	39-1/4 x 37-5/8 x 14-5/8	39-1/4 x 37-5/8 x 16-1/2
Net Weight	lb	32	34	56	59.5	70.5
Gross Weight	lb	38.5	40.5	76	79.5	90.5
DUCTED UNIT						
Sound Pressure Level (H/M/L)	dB(A)	35/33/32	36/34/33	38/37/36	42/38/36	43/40/38
Dimension (WxHxD)	inch	35 7/8 x 7 1/2 x 17 5/8	35 7/8 x 7 1/2 x 17 5/8	46 1/2 x 7 1/2 x 17 5/8	35 3/8 x 10 5/8 x 28 3/8	51 1/8 x 13 3/8 x 31 1/2
Package Dimension (WxHxD)	inch	42 1/2 x 11 1/4 x 22 1/4	43 1/2 x 11 1/4 x 22 1/4	53 1/8 x 11 1/4 x 22-1/4	46 x 13-3/8 x 34 1/4	61 x 16 1/8 x 37
Net Weight	lb	39.7	39.7	49.6	66.1	112.4
Gross Weight	lb	46.3	46.3	57.3	77.2	132.3
OUTDOOR UNIT						
Sound Pressure Level	dB(A)	52	52	55	55	61
Dimension (WxHxD)	inch	31 7/8 x 22 7/8 x 11	31 7/8 x 22 7/8 x 11	33 7/8 x 26 3/8 x 12 1/4	37 3/8 x 33 1/8 x 13 3/8	37 3/8 x 41 3/8 x 13 3/8
Package Dimension (WxHxD)	inch	37 x 25 1/4 x 16 1/2	37 x 25 1/4 x 16 1/2	39 3/16 x 28 3/4 x 17 3/4	43 3/4 x 36 1/4 x 18 1/8	43 3/4 x 47 1/4 x 18 1/8
Net Weight	lb	75	79.4	105.8	155.1	192
Gross Weight	lb	83.8	88.2	114.6	166.4	214.5
Refrigerant	-	R410A	R410A	R410A	R410A	R410A
PIPE CONNECTION						
Refrigerant Charge	oz	33.5	45.9	56.44	91.7	111.2
Connection Pipe Length	ft	25	25	25	25	25
Connection Pipe Gas Additional Charge	oz/ft	0.161	0.161	0.161	0.376	0.376
Outer Diameter Liquid Pipe	inch	1/4	1/4	1/4	3/8	3/8
Outer Diameter Gas Pipe	inch	3/8	3/8	1/2	5/8	3/4
Max Distance Height	ft	33	33	49	98	98
Max Distance Length	ft	82	82	98	164	164



Air-Con International, Inc.
1802 SW 2nd St
Pompano Beach, FL 33069
Ph: 954-771-1415



www.airconint.com

Air-Con International, Inc. - Miami
7108 NW 50th St
Miami, FL 33166
Ph: 786-238-7234