



Up to 15 SEER • From 18 to 36K BTU



Heat & Cool

Heat pump air conditioners can both heat & cool. All models are SEER2 compliant.



Accepts Any Standard Thermostat

The Saturn Series units are equipped to connect easily to standard home thermostats.



Each unit is covered with our Industry Leading Warranty. *Registration requirements vary by state.*

For full warranty policy details, visit:

airconint.com/warranty-information



Condenser (ODU)



Model			ATSCV4H4T18	ATSCV4H4T24	ATSCV4H4T30	ATSCV4H4T36
Outdoor power supply		V/Ph/Hz	230V/1N/60HZ	230V/1N/60HZ	230V/1N/60HZ	230V/1N/60HZ
Cooling	Capacity	Btu/h	17500	22000	28000	33000
	Input	W	1550	2000	2370	2780
	EER2	Btu/h.W	11.50	11.20	11.50	11.50
	SEER2 (AHRI Certified)	Btu/h.W	14.3	14.3	14.3	14.3
Heating	Capacity	Btu/h	17500	22000	26000	33000
	HSPF2(AHRI Certified)	Btu/h.W	7.50	7.50	7.50	7.50
Max. input consumption		W	2250.00	3050.00	3300.00	4455.00
Max. current		A	11.50	15.00	17.00	23.00
Outdoor air flow		CFM	2000	2000	2250	2750
Outdoor sound pressure level		dB(A)	60	60	63	63
Outdoor dimension	Unit (W*H*D)	in	23-3/5*25*23-3/5	23-3/5*25*23-3/5	23-3/5*25*23-3/5	29-1/7*25*29-1/7
		mm	600*633*600	600*633*600	600*633*600	740*633*740
	Packing (W*H*D)	in	24-4/5*26-1/5*24-4/5	24-4/5*26-1/5*24-4/5	24-4/5*26-1/5*24-4/5	30-3/10*26-1/5*30-3/10
		mm	630*665*630	630*665*630	630*665*630	770*665*770
	Net / Gross weight	kg	57.5/60	58.5/61	66/68.5	75.5/78.5
		lbs	127/132	129/134	146/151	166/173
Refrigerant	Type		R410A	R410A	R410A	R410A
	Charging volume	oz	93.50	98.80	105.80	123.50
Refrigerant pipe	Liquid side	in	Φ3/8	Φ3/8	Φ3/8	Φ3/8
	Gas side	in	Φ3/4	Φ3/4	Φ3/4	Φ3/4
	Max. refrigerant pipe length	ft	148	148	148	148
	Max. difference in level	ft	66	66	66	66



Front Return Air Handler (IDU)

Model			ATSEFR4H4T18	ATSEFR4H4T24	ATSEFR4H4T30	ATSEFR4H4T36
Power supply		V/Ph/Hz	208~230V/1N/60Hz	208~230V/1N/60Hz	208~230V/1N/60Hz	208~230V/1N/60Hz
Cooling	Capacity	Btu/h	17500	22000	28000	33000
	SEER2	Btu/h.W	14.30	14.30	14.30	14.30
Indoor air flow		CFM	715	805	1020	1145
Indoor sound pressure level		dB(A)	/	/	/	/
Indoor dimension	Unit (W*H*D)	in	20-3/5*36*15	20-3/5*36*15	22-1/10*39-3/5*19	22-1/10*39-3/5*19
		mm	524*915*381	524*915*381	562*1006*485	562*1006*485
	Packing (W*H*D)	in	23-1/5*39-2/5*17-7/10	23-1/5*39-2/5*17-7/10	24-3/5*42-9/10*21-3/5	24-3/5*42-9/10*21-3/5
		mm	590*1000*450	590*1000*450	625*1090*550	625*1090*550
	Net / Gross weight	kg	40/44	40/44	51/56	51/56
		lbs	88/97	88/97	112/123	112/123
Refrigerant pipe	Liquid side	in	3/8	3/8	3/8	3/8
	Gas side	in	3/4	3/4	3/4	3/4



Air-Con International, Inc.
2031 SW 2nd St
Pompano Beach, FL 33069
Ph: 954-771-1415



www.airconint.com

Air-Con International, Inc. - Miami
7108 NW 50th St
Miami, FL 33166
Ph: 786-238-7234